D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko	
Date of Inspection: Dec 1, 12	Time: 5:00
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: ISOBUTELENE	
Background Instrument Reading:	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	220	0		A	N	—	—	—
ATDU / OWS	Running	Down	1928	12.1	1.7	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1761	4.2	1.2	A	N	—	—	—
Distillation Unit	Running	Down	2181	7.3	0.2	A	N	—	—	—
Tank 51	Running	Down	1901	2.1	0.9	A	N	—	—	—
Tank 55	Running	Down	2068	3.2	0.2	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Rick PALOMO
Date of Inspection: 12/1/12	Time: 5:00 PM
Shift: (First or Second)	FIRST
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	ISOBUTYLENE 100PPM
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	175	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1954	0	3.6	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	2350	5.7	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	2791	0	2.1	A	N	—	—	—
Tank 51	Running ✓	Down	2919	3.4	0	A	N	—	—	—
Tank 55	Running ✓	Down	3055	0	7.9	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Ted Compton	
Date of Inspection: 12/2/12	Time: 5:00 PM
Shift: (First) or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene 100PPM	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	188			A	N	—	—	—
ATDU / OWS	Running ✓	Down	1925	0	3.8	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	2999	0	6.7	A	N	—	—	—
Distillation Unit	Running ✓	Down	3766	0	4.4	A	N	—	—	—
Tank 51	Running ✓	Down	3945	0	1.9	A	N	—	—	—
Tank 55	Running ✓	Down	2145	0	3.3	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko

Date of Inspection: Dec Time: 5:00

Shift: (First or Second)

Monitor ID: Mini Rae 2000

Instrument Calibration Gases: ISOBUTYLENE 100ppm

Background Instrument Reading: 00

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	168	0		A	N	—	—	—
ATDU / OWS	Running	Down	1291	2.3	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1928	4.1	0	A	N	—	—	—
Distillation Unit	Running	Down	1601	3.6	0	A	N	—	—	—
Tank 51	Running	Down	2068	2.7	0	A	N	—	—	—
Tank 55	Running	Down	1871	4.9	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Rick Palomo
Date of Inspection: 12/3/12	Time: 5:00 AM
Shift: (First or Second)	second
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	Isobutylene/Air
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement Y/N	Carbon Replacement Date	Carbon Replacement Time	Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	177	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1877	0	4.7	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	3921	9.2	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	5744	0	5.3	A	N	—	—	—
Tank 51	Running ✓	Down	6321	7.9	0	A	N	—	—	—
Tank 55	Running ✓	Down	4798	0	8.2	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko	
Date of Inspection: Dec 3, 12	Time: 5:00
Shift: (First) or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: ISOBUTENE	
Background Instrument Reading: 00	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	175	0		A	N	—	—	—
ATDU / OWS	Running	Down	1829	3.2	.7	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1765	2.8	1.3	A	N	—	—	—
Distillation Unit	Running	Down	1901	4.7	2.1	A	N	—	—	—
Tank 51	Running	Down	2088	3.6	2.9	A	N	—	—	—
Tank 55	Running	Down	2341	4.1	3.1	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko

Date of Inspection: Dec 4, 12 | Time: 5:00

Shift: (First) or Second)

Monitor ID: Mini Rae 2000

Instrument Calibration Gases: ISOBUTLYENE

Background Instrument Reading:

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement Y/N	Carbon Replacement Date	Carbon Replacement Time	Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
Vapor Recovery System: CARBON OR (FLARE)	(Running)	Down	0	0		A	N	—	—	—
SDS Shredder	(Running)	Down	191	0		A	N	—	—	—
ATDU / OWS	(Running)	Down	1188	.4	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	(Running)	Down	1799	1.7	0	A	N	—	—	—
Distillation Unit	(Running)	Down	2309	2.8	0	A	N	—	—	—
Tank 51	(Running)	Down	1637	.3	0	A	N	—	—	—
Tank 55	(Running)	Down	1929	4.1	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Rick PALOMO

Date of Inspection: 12/5/12 Time: 5:00 AM

Shift: (First or Second) second

Monitor ID: Mini Rae 2000

Instrument Calibration Gases: ISO BUTYLENE 100PPM

Background Instrument Reading: 0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	177	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1351	0	2.1	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	3000	5.9	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	3841	0	7.4	A	N	—	—	—
Tank 51	Running ✓	Down	2541	2.9	0	A	N	—	—	—
Tank 55	Running ✓	Down	2351	0	3.7	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: RICK PALOMO	
Date of Inspection: 12/5/12	Time: 5:00 AM
Shift: (First or Second) Second	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: ISOBUTYLENE 100 PPM	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	177	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1357	0	2.7	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1751	3.1	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	2357	4.3	0	A	N	—	—	—
Tank 51	Running ✓	Down	2475	7.1	0	A	N	—	—	—
Tank 55	Running ✓	Down	2741	0	4.4	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko

Date of Inspection: Dec 5 12 | Time: 5:00

Shift: (First or Second)

Monitor ID: Mini Rae 2000

Instrument Calibration Gases: ISOBUTYLENE

Background Instrument Reading: 00

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	278	0		A	N	—	—	—
ATDU / OWS	Running	Down	1501	1.3	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1116	.2	0	A	N	—	—	—
Distillation Unit	Running	Down	1729	4.7	0	A	N	—	—	—
Tank 51	Running	Down	1862	3.2	0	A	N	—	—	—
Tank 55	Running	Down	1509	1.4	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	RICK PALOMO
Date of Inspection: 12/6/12	Time: 5:00 AM
Shift: (First or Second)	Second
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	ISOBUTYLENE 100 PPM
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	155	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	3576	19.2	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	2856	0	21.7	A	N	—	—	—
Distillation Unit	Running ✓	Down	6957	35.4	0	A	N	—	—	—
Tank 51	Running ✓	Down	3918	20.8	0	A	N	—	—	—
Tank 55	Running ✓	Down	1869	0	12.2	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko

Date of Inspection: Dec 6, 12 Time: 5:00

Shift: (First) or Second)

Monitor ID: Mini Rae 2000

Instrument Calibration Gases: ISOBUTYLENE

Background Instrument Reading: 00

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement Y/N	Carbon Replacement Date	Carbon Replacement Time	Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	199	0		A	N	—	—	—
ATDU / OWS	Running	Down	2018	1.4	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1716	2.6	0	A	N	—	—	—
Distillation Unit	Running	Down	1937	2.1	0	A	N	—	—	—
Tank 51	Running	Down	1801	5.1	0	A	N	—	—	—
Tank 55	Running	Down	1621	3.2	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: RICK PALOMO

Date of Inspection: 12/7/12 Time: 5:00 AM

Shift: (First or Second) Second

Monitor ID: Mini Rae 2000

Instrument Calibration Gases: ISOBUTYLENE 100PPM

Background Instrument Reading: 0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	——		A	N	—	—	——
SDS Shredder	Running ✓	Down	175	0		A	N	—	—	——
ATDU / OWS	Running ✓	Down	3257	0	12.9	A	N	—	—	——
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1988	4.7	0	A	N	—	—	——
Distillation Unit	Running ✓	Down	6312	0	13.7	A	N	—	—	——
Tank 51	Running ✓	Down	4632	17.5	0	A	N	—	—	——
Tank 55	Running ✓	Down	1978	0	6.4	A	N	—	—	——

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko

Date of Inspection: Dec 7, 12 Time: 5:00

Shift: (First or Second)

Monitor ID: Mini Rae 2000

Instrument Calibration Gases: ISOBUTYLENE

Background Instrument Reading: 00

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement Y/N	Carbon Replacement Date	Carbon Replacement Time	Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	1201	0		A	N	—	—	—
ATDU / OWS	Running	Down	1637	3.2	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1801	5.1	0	A	N	—	—	—
Distillation Unit	Running	Down	1766	7.2	0	A	N	—	—	—
Tank 51	Running	Down	2131	1.3	0	A	N	—	—	—
Tank 55	Running	Down	1899	2.9	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: RICK PALOMO
Date of Inspection: 12/8/12 Time: 5:00 PM
Shift: (First or Second) FIRST
Monitor ID: Mini Rae 2000
Instrument Calibration Gases: ISOBUTYLENE 100PPM
Background Instrument Reading: 0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement Y/N	Carbon Replacement Date	Carbon Replacement Time	Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	298	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1221	0	2.9	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1999	3.4	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	2810	0	5.7	A	N	—	—	—
Tank 51	Running ✓	Down	4249	3.2	0	A	N	—	—	—
Tank 55	Running ✓	Down	3517	0	14.9	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	R Lows
Date of Inspection: 12/8/12	Time: 5 Am
Shift: (First or ~~Second~~)	SECOND
Monitor ID:	MINI RAE 2000
Instrument Calibration Gases:	ISOBUTYLENE 100 ppm
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR ~~FLARE~~	Running ✓	Down	—	—		A	N	/	/	/
SDS Shredder	Running ✓	Down	320	0.0		A	N	/	/	/
ATDU / OWS	Running ✓	Down	2790	6	Ø	A	N	/	/	/
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	2150	6	Ø	A	N	/	/	/
Distillation Unit	Running ✓	Down	3140	4	Ø	A	N	/	/	/
Tank 51	Running ✓	Down	990	2	Ø	A	N	/	/	/
Tank 55	Running ✓	Down	1420	2	Ø	NA	N	/	/	/

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

MW

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko

Date of Inspection: Dec 9, 12 Time: 5:00

Shift: (First) or Second)

Monitor ID: Mini Rae 2000

Instrument Calibration Gases: ISOBUTYLENE

Background Instrument Reading: 00

unit down

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	(Down)	0	0		A	N	—	—	—
SDS Shredder	Running	(Down)	260	0		A	N	—	—	—
ATDU / OWS	(Running)	Down	1721	1.3	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	(Running)	Down	1509	3.2	0	A	N	—	—	—
Distillation Unit	(Running)	Down	1961	2.7	0	A	N	—	—	—
Tank 51	(Running)	Down	1801	4.6	0	A	N	—	—	—
Tank 55	(Running)	Down	1529	5.0	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

UNIT DOWN

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	RICK RACOMO
Date of Inspection: 12/10/12	Time: 5:00 AM
Shift: (First or Second)	second
Monitor ID:	Min. Rae 2000
Instrument Calibration Gases:	ISOBUTYLENE 100PPM
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down ✓	—	—		A	N	—	—	—
SDS Shredder	Running	Down ✓	377	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1831	0	2.1	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	3911	3.9	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	4257	0	4.7	A	N	—	—	—
Tank 51	Running ✓	Down	2351	5.6	0	A	N	—	—	—
Tank 55	Running ✓	Down	1987	0	11.3	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

UNIT DOWN

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Rick Palomo
Date of Inspection: 12/10/12	Time: 5:00 AM
Shift: (First or Second)	second
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	ISOBUTYLENE 100PPM
Background Instrument Reading:	0, 0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down ✓	—	—		A	N	—	—	—
SDS Shredder	Running	Down ✓	391	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1831	0	2.1	A	N	—	—	—
Area 8 - Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	3911	3.9	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	4257	0	4.7	A	N	—	—	—
Tank 51	Running ✓	Down	2351	5.6	0	A	N	—	—	—
Tank 55	Running ✓	Down	1987	0	11.3	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko	
Date of Inspection: Dec 11, 12	Time: 5:00
Shift: (First) or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: ISOBUTENE	
Background Instrument Reading:	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	(Running)	Down	0	0		A	N	—	—	—
SDS Shredder	(Running)	Down	196	0		A	N	—	—	—
ATDU / OWS	(Running)	Down	1801	4.2	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	(Running)	Down	1765	1.5	0	A	N	—	—	—
Distillation Unit	(Running)	Down	1927	.02	0	A	N	—	—	—
Tank 51	(Running)	Down	2009	1.3	0	A	N	—	—	—
Tank 55	(Running)	Down	1626	4.2	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITOR

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU/OWS, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

UNIT DOWN

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: RICK PALOMO	Time: 5:00 AM
Date of Inspection: 12/11/12	
Shift: (First or Second) Second	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: ISOBUTYLENE 100 PPM	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down ✓	—	—		A	N	-	-	—
SDS Shredder	Running	Down ✓	297	0	13.2	A	N	-	-	—
ATDU / OWS	Running ✓	Down	1454	5.1	0	A	N	-	-	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	2764	0	3.9	A	N	-	-	—
Distillation Unit	Running ✓	Down	3002	7.8	0	A	N	-	-	—
Tank 51	Running ✓	Down	1798	0	5.1	A	N	-	-	—
Tank 55	Running ✓	Down	3251							

D. 1. CARBON ADSORPTION MONITORING LOG FOR

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Rick PALOMO	
Date of Inspection: 12/12/12	Time: 5:00 AM
Shift: (First or Second) Second	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: ISOBUTYLENE 100PPM	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	489	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1395	0	2.1	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	2154	5.7	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	3901	0	9.2	A	N	—	—	—
Tank 51	Running ✓	Down	4202	11.7	0	A	N	—	—	—
Tank 55	Running ✓	Down	3577	0	17.9	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Dist...
and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko
Date of Inspection: Dec 12, 12 Time: 5:00
Shift: (First) or Second)
Monitor ID: Mini Rae 2000
Instrument Calibration Gases: ISOBUTYLENE 10 ppm
Background Instrument Reading: 00

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement Y/N	Carbon Replacement Date	Carbon Replacement Time	Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
Vapor Recovery System: CARBON OR (FLARE*)	(Running)	Down	0	0		A	N	—	—	—
SDS Shredder	(Running)	Down	0	0		A	N	—	—	—
ATDU / OWS	(Running)	Down	268	0	4.7	A	N	—	—	—
Area 8 - – Tanks 52,53;54 (Tanks 02 through 04)	(Running)	Down	1767	1.2	0	A	N	—	—	—
Distillation Unit	(Running)	Down	1629	0	2.3	A	N	—	—	—
Tank 51	(Running)	Down	1981	4.6	0	A	N	—	—	—
Tank 55	(Running)	Down	1401	0	5.2	A	N	—	—	—
			1766							

D. 1. CARBON ADSORPTION MONITORING

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distil... and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Rick PALOMC
Time: 5:00 AM
Date of Inspection: 12/13/12
Shift: (First or Second) Second
Monitor ID: Mini Rae 2000
Instrument Calibration Gases: ISOBUTYLENE 100PPM
Background Instrument Reading: 0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement Y/N	Carbon Replacement Date	Carbon Replacement Time	Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down								
Vapor Recovery System:			—	—		A	N	—	—	—
CARBON OR FLARE*	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	173	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	2157	0	2.1	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1477	7.9	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	3912	17.2	0	A	N	—	—	—
Tank 51	Running ✓	Down	1998	0	11.9	A	N	—	—	—
Tank 55	Running ✓	Down	5471	5.7	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Rick Palomo	Time: 5:00 AM
Date of Inspection: 12/14/12	
Shift: (First or Second) Second	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene 100ppm	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	177	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	2157	0	2.1	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	2871	3.7	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	3099	0	4.2	A	N	—	—	—
Tank 51	Running ✓	Down	2951	3.9	0	A	N	—	—	—
Tank 55	Running ✓	Down	3157	0	7.9	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Rick PALOMO	Time: 5:00 PM
Date of Inspection: 12/15/12	
Shift: (First or Second) Second	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: ISOBUTYLENE 100PPM	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	177	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	2151	0	2.1	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1998	5.7	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	3211	0	3.9	A	N	—	—	—
Tank 51	Running ✓	Down	1751	12.2	0	A	N	—	—	—
Tank 55	Running ✓	Down	3151	0	9.3	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Ted Compton	
Date of Inspection: 12/16/12	Time: 5:00 AM
Shift: (First or (Second))	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene 100PPM	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement Y/N	Carbon Replacement Date	Carbon Replacement Time	Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
	Running	Down								
Vapor Recovery System:			—	—		A	N	—	—	—
CARBON OR (FLARE*)	✓			0		A	N	—	—	—
SDS Shredder	✓		156		3.1	A	N	—	—	—
ATDU / OWS	✓		2234	0	4.8	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	✓		2277	0	4.7	A	N	—	—	—
Distillation Unit	✓		2918	0	9.7	A	N	—	—	—
Tank 51	✓		1999	0	8.6	A	N	—	—	—
Tank 55	✓		2777							

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Darren B Cudjoe	
Date of Inspection: 12/16/2012	Time: 5:30 pm
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene	100ppm
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	156	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	2240	6	3.1	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	2260	0	4.8	A	N	—	—	—
Distillation Unit	Running ✓	Down	29	0	4.7	A	N	—	—	—
Tank 51	Running ✓	Down	1997	0	8.3	A	N	—	—	—
Tank 55	Running ✓	Down	2777	0	7.4	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: RICK PALOMO
Time: 5:00 AM
Date of Inspection: 12/17/12
Shift: (First or Second) Second
Monitor ID: Mini Rae 2000
Instrument Calibration Gases: ISOBUTYLENE 100PPM
Background Instrument Reading: 0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	1199	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1351	0	2.1	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1753	9.1	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	2310	0	7.2	A	N	—	—	—
Tank 51	Running ✓	Down	1855	3.1	0	A	N	—	—	—
Tank 55	Running ✓	Down	3217	0	5.1	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITOR

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU / OWS and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko
Time: 500
Date of Inspection: Dec 19, 12
Shift: (First) or Second)
Monitor ID: MiniRae 2000
Instrument Calibration Gases: ISOBUTYLENE
Background Instrument Reading: 00

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System:	Running	Down	0	0		A	N	—	—	—
CARBON OR FLARE*	Running	Down	260	0		A	N	—	—	—
SDS Shredder	Running	Down	1781	0.2	0	A	N	—	—	—
ATDU / OWS	Running	Down	1651	2.7	1.2	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	2128	4.6	0	A	N	—	—	—
Distillation Unit	Running	Down	1926	3.2	3.4	A	N	—	—	—
Tank 51	Running	Down	1501	0.1	4.1	A	N	—	—	—
Tank 55										

Revised 2/10/09

D. 1. CARBON ADSORPTION MONITORING LOG FOR B...

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Rick PALOMO
Time: 5:00 AM
Date of Inspection: 12/18/12
Shift: (First or Second) Second
Monitor ID: Mini Rae 2000
Instrument Calibration Gases: ISOBUTYLENE 100PPM
Background Instrument Reading: 0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	832	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1375	0	2.9	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1751	3.9	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	4988	0	7.5	A	N	—	—	—
Tank 51	Running ✓	Down	1541	13.9	0	A	N	—	—	—
Tank 55	Running ✓	Down	3812	0	7.9	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

UNIT DOWN

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Rick PALOMO	
Date of Inspection: 12/19/12	Time: 5:00 AM
Shift: (First or Second)	second
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	ISOBUTYLENE 100 PPM
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down ✓	—	—		A	N	—	—	—
SDS Shredder	Running	Down ✓	475	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	2817	2.9	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	899	0	5.2	A	N	—	—	—
Distillation Unit	Running ✓	Down	3857	13.2	0	A	N	—	—	—
Tank 51	Running ✓	Down	4651	15.4	0	A	N	—	—	—
Tank 55	Running ✓	Down	2209	0	7.2	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR B

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko

Date of Inspection: Dec 19, 12 Time: 5:00

Shift: (First) or Second)

Monitor ID: Mini Rae 2000 100ppm

Instrument Calibration Gases: ISOBUTELENE

Background Instrument Reading: 00

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement Y/N	Carbon Replacement Date	Carbon Replacement Time	Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
Vapor Recovery System: CARBON OR (FLARE)*	(Running)	Down	0	0		A	N	—	—	—
SDS Shredder	(Running)	Down	3207	0		A	N	—	—	—
ATDU / OWS	(Running)	Down	1599	1.2	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	(Running)	Down	1901	0	3.4	A	N	—	—	—
Distillation Unit	(Running)	Down	1657	3.2	0	A	N	—	—	—
Tank 51	(Running)	Down	2001	0	3.9	A	N	—	—	—
Tank 55	(Running)	Down	1961	5.6	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

Unit Down

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko	
Date of Inspection: Dec 20, 12	Time: 5:00
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: ISOBUTELNE	
Background Instrument Reading:	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	190	0		A	N	—	—	—
ATDU / OWS	Running	Down	1765	2.1	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1829	1.4	0	A	N	—	—	—
Distillation Unit	Running	Down	1561	3.7	0	A	N	—	—	—
Tank 51	Running	Down	1791	4.2	0	A	N	—	—	—
Tank 55	Running	Down	1899	2.1	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Rick PALOMC
Date of Inspection: 12/20/12	Time: 5:00 AM
Shift: (First or Second)	Second
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	ISOBUTYLENE 100PPM
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	—	—	—
SDS Shredder	Running ✓	Down	217	0		A	N	—	—	—
ATDU / OWS	Running ✓	Down	1599	0	2.1	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	2157	7.3	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	3052	0	15.3	A	N	—	—	—
Tank 51	Running ✓	Down	2761	9.2	0	A	N	—	—	—
Tank 55	Running ✓	Down	3999	0	17.9	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

UNIT DOWN

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Rick PALOMO
Date of Inspection: 12/21/12	Time: 5:00 AM
Shift: (First or Second)	Second
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	ISOBUTYLENE
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement Y/N	Date	Time	Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
Vapor Recovery System: CARBON OR FLARE*	Running	Down ✓	—	—		A	N	—	—	—
SDS Shredder	Running	Down ✓	241	0		A	N	—	—	—
ATDU / OWS	Running	Down ✓	1221	0	17.3	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	1763	15.2	0	A	N	—	—	—
Distillation Unit	Running ✓	Down	2154	0	9.3	A	N	—	—	—
Tank 51	Running ✓	Down	1998	6.8	0	A	N	—	—	—
Tank 55	Running	Down ✓	1371	0	4.2	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko

Date of Inspection: Dec 21, 12 | Time: 500

Shift: (First) or Second)

Monitor ID: Mini Rae 2000

Instrument Calibration Gases: ISOBUTENE

Background Instrument Reading: 00

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement Y/N	Carbon Replacement Date	Carbon Replacement Time	Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
Vapor Recovery System: CARBON OR FLARE*	Running	(Down)	0	0		A	N	—	—	—
SDS Shredder	Running	(Down)	301	0		A	N	—	—	—
ATDU / OWS	Running	(Down)	1268	1,2	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running	(Down)	1729	3.4	0	A	N	—	—	—
Distillation Unit	Running	(Down)	1938	5.1	0	A	N	—	—	—
Tank 51	Running	(Down)	1528	3.1	0	A	N	—	—	—
Tank 55	Running	(Down)	1401	2.7	0	A	N	—	—	—

Unit down

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko

Date of Inspection: Dec 26 Time: 5:00

Shift: (First) or Second)

Monitor ID: Mini Rae 2000

Instrument Calibration Gases: ISO BUTYLENE

Background Instrument Reading: 00

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement Y/N	Carbon Replacement Date	Carbon Replacement Time	Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	1216	0		A	N	—	—	—
ATDU / OWS	Running	Down	1981	1.4	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	2102	4.7	0	A	N	—	—	—
Distillation Unit	Running	Down	1766	5.0	0	A	N	—	—	—
Tank 51	Running	Down	1509	3.2	0	A	N	—	—	—
Tank 55	Running	Down	2126	3.6	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko	
Date of Inspection: Dec 27, 12	Time: 5:00
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: ~~Mini Rae~~ Isobutylene	
Background Instrument Reading: 00	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	~~Running~~	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	260	0		A	N	—	—	—
ATDU / OWS	Running	Down	1928	2.3	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1765	4.7	0	A	N	—	—	—
Distillation Unit	Running	Down	2309	1.7	0	A	N	—	—	—
Tank 51	Running	Down	1946	2.8	0	A	N	—	—	—
Tank 55	Running	Down	1751	3.7	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko	
Date of Inspection: Dec 28 '12	Time: 5:00
Shift: (First or Second)	
Monitor ID: MiniRae 2000	
Instrument Calibration Gases: ISOBUTENE	
Background Instrument Reading: 00	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR (FLARE*)	Running	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	357	0		A	N	—	—	—
ATDU / OWS	Running	Down	1801	2.1	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1729	4.7	0	A	N	—	—	—
Distillation Unit	Running	Down	1688	3.2	0	A	N	—	—	—
Tank 51	Running	Down	1401	5.8	0	A	N	—	—	—
Tank 55	Running	Down	1566	1.2	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Rick PALOMO
Date of Inspection: 12/28/12 Time: 5:00 AM
Shift: (First or Second) Second
Monitor ID: Mini Rae 2000
Instrument Calibration Gases: ISOBUTYLENE 100 PPM
Background Instrument Reading: 0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement Y/N	Carbon Replacement Date	Carbon Replacement Time	Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
Vapor Recovery System: CARBON OR FLARE*	Running ✓	Down	—	—		A	N	–	–	—
SDS Shredder	Running ✓	Down	319	0		A	N	–	–	—
ATDU / OWS	Running ✓	Down	7243	197.7	26.44	A	Y	12/28/12	5:00 AM	462
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running ✓	Down	3021	0	7.9	A	N	–	–	—
Distillation Unit	Running ✓	Down	2272	3.4	0	A	N	–	–	—
Tank 51	Running ✓	Down	3052	0	5.6	A	N	–	–	—
Tank 55	Running ✓	Down	2639	14.2	0	A	N	–	–	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Ted Compton	
Date of Inspection: 12/29/12	Time: 5:00PM
Shift: (First) or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: Isobutylene 100PPM	
Background Instrument Reading: 0.0	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	—	—		A	N	—	—	—
SDS Shredder	Running	Down	134	0		A	N	—	—	—
ATDU / OWS	Running	Down	914	0	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	Running	Down	1117	0	6.1	A	N	—	—	—
Distillation Unit	Running	Down	2233	0	0.7	A	N	—	—	—
Tank 51	Running	Down	2468	0	3.4	A	N	—	—	—
Tank 55	Running	Down	1729	0	2.2	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Stagner	
Date of Inspection: 12/30/12	Time: @ 0600
Shift: (First or (Second))	Second
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	100% Isobutylene
Background Instrument Reading:	0.0

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR (FLARE*)	(Running)	Down	—	—		A	N	—	—	—
SDS Shredder	(Running)	Down	187	Ø		A	N	—	—	—
ATDU / OWS	(Running)	Down	729	Ø	—	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	(Running)	Down	853	112	Ø	A	N	—	—	—
Distillation Unit	(Running)	Down	1768	97	Ø	A	N	—	—	—
Tank 51	(Running)	Down	2163	149	Ø	A	N	—	—	—
Tank 55	(Running)	Down	1219	82	Ø	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector: Smelko	
Date of Inspection: Dec 30, 12	Time: 5.00
Shift: (First or Second)	
Monitor ID: Mini Rae 2000	
Instrument Calibration Gases: ISOBUTELYENE	
Background Instrument Reading: 00	

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR (FLARE*)	(Running)	Down	0	0		A	N	—	—	—
SDS Shredder	(Running)	Down	1728	0		A	N	—	—	—
ATDU / OWS	(Running)	Down	1937	3.7	0	A	N	—	—	—
Area 8 - – Tanks 52,53,54 (Tanks 02 through 04)	(Running)	Down	5928	4.9	0	A	N	—	—	—
Distillation Unit	(Running)	Down	8129	3.8	0	A	N	—	—	—
Tank 51	(Running)	Down	3200	2.9	0	A	N	—	—	—
Tank 55	(Running)	Down	1568	1.3	0	A	N	—	—	—

D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY

Condition D.1.10 Carbon Adsorber/Canister Monitoring
Condition D.1.17 Record Keeping Requirements (c)
PCI shall document compliance by monitoring for VOC breakthrough at least once per shift when the SDS shredder, the ATDU, the Distillation Unit, and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note.

D.1.14 CARBON ADSORPTION SYSTEM INSPECTION

Inspector:	Smelko
Date of Inspection: Dec 30 12	Time: 500
Shift: (First or Second)	
Monitor ID:	Mini Rae 2000
Instrument Calibration Gases:	ISOBUTEYENE
Background Instrument Reading:	00

Location of Carbon Control Device	Unit Status		Inlet	Exhaust		Visual Insp.	Carbon Replacement			Spent Carbon Placed in Roll Off Box No. for Offsite Combustion
							Y/N	Date	Time	
Vapor Recovery System: CARBON OR FLARE*	Running	Down	0	0		A	N	—	—	—
SDS Shredder	Running	Down	296		0	A	N	—	—	—
ATDU / OWS	Running	Down	1508	3.7	0	A	N	—	—	—
Area 8 - – Tanks 52,53;54 (Tanks 02 through 04)	Running	Down	2988	2.1	0	A	N	—	—	—
Distillation Unit	Running	Down	1796	4.6	0	A	N	—	—	—
Tank 51	Running	Down	1821	5.2	0	A	N	—	—	—
Tank 55	Running	Down	2235	1.0	0	A	N	—	—	—